



SHORT FORM

Gecko Alliance Gr
Unauthorized copy

Specificati SP820
Specificati Ab0
Software n 186
Software n 1
Gecko Dep

Customer

Important: A differ

Config. #	OUT 1	OUT 2	OUT 3	OUT 4	OUT 5	OUT 6	OUT 7	OUT 8	CP configuration	Ozone configuration	Filter Type	Heater Pump
1		-	P1 1sp	Ozone	-	>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
2			P1 1sp	Ozone	>Blower	>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
3		>P2 1sp	P1 1sp	Ozone		>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
4		>P2 1sp	P1 1sp	Ozone	>Blower	>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
5	P3	>P2 1sp	P1 1sp	Ozone		>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
6	P3	>P2 1sp	P1 1sp	Ozone	>Blower	>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
7	P3	>P2 1sp	P1 & P4	Ozone		>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
8	P3	>P2 1sp	P1 & P4	Ozone	>Blower	>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
9	P3	P2 & P5	P1 & P4	Ozone		>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP
10	P3	P2 & P5	P1 & P4	Ozone	>Blower	>CP	Always ON	Direct	During filtration	On during Filter cycle, with CP	Clean, CP	CP

I acknowlec

Authorised cus

Date

Note:

OPTIONS (

Water temperature control	Sanitation options (if used)	Variable speed pump options (if used)
Temperatur °C	Level: 2	Check flow 2000 %
Default set 35 °C	On time: 30	Filter spee 1000 %
Over Set Po >Disable	Ozen options (if used)	Pump spee 4000 %
External ch >Disable	Default start tin 12:00	Pump spee 6000 %
User demands options	Default duratio 2:00	Pump spee 10000 %
Pump timec 20	Default frequer >2	Current limitations & ratings
Light timeot 120	Economy options	Main suppl CE
Fiber box til 120	Manual econor Enable	Default nu 1
Number of l >1	Program econc Enable	CE 2 x 20/ Enable
Blower key: >Last pump ke	Prog. Economy >Disable	Line frequ 50 Hz
Quick On/C >Disable	Start Time: 23:00	Line voltag 230 Vac
120/230V L >Follow 12V Li	Stop Time: 15:00	Heat exclu >Yes
Filter and ozone options	Set point drop: 20 °f	Number of 4
Default star 8:00	Quiet mode options	Default bre 3
Default dur 2:00	Quiet type: >Pause us	Breaker cu 16 a
Default freq >2	User demands >Exit quiet	Breaker cu 20 a
Filter suspend by: >Pump User D	Old user dema >Cancel	Breaker cu 32 a
Filter suspend time: 40	Quiet timeout: 30	Breaker cu 40 a
Purge spee >High	Quiet heater ac >Keep hea	Breaker cu
Ozone suspend by: >Pump User D	Miscellaneous Configuration	Pump 1 Hi 0.0 A
Ozone susp 40	Time Format: >24h	Pump 1 Lc 0.0 A
Ozone filter 1	IN.K600 Spec: >Disable	Pump 2 Hi 0.0 A

